

Technical data sheet

Push-fit plug Delta-Push® for pushing in

Item number: 2351670



Push-fit plug Delta-Push® for mounting electrical installations. Suitable for concrete, calcareous limestone, full brick, hollow brick and porous concrete. Toolless mounting by pushing into a drill hole in a wall or on a ceiling. Without screws. To install cable trunking or labelling panels, for example.



PA Polyamide

Master data

| | |
|---------------------|-----------------|
| Item number | 2351670 |
| Description 1 | Push-fit plug |
| Description 2 | for pressing in |
| Available from | 01.02.2025 |
| Manufacturer | OBO |
| Dimension | 34,2x14,2x12,2 |
| Material | Polyamide |
| Smallest sales unit | 100 |
| Unit of quantity | Piece |
| Weight | 0.083 kg |
| Weight unit | kg/100 pc. |


Technical data sheet

Push-fit plug Delta-Push® for pushing in

Item number: 2351670



Dimensions



Length 30 mm

Technical data

| | |
|--|---|
| Version for | Push-fit anchor |
| Drill hole depth | 35 mm |
| Drill hole diameter, min. | 6 mm |
| Suitable for fastening with cable ties | no |
| Suitable for gas concrete | yes |
| Suitable for hexagonal wood screw | no |
| Halogen-free | yes |
| With edge | no |
| With bolts | no |
| Suitable for material | Calcareous sandstone Porous concrete Concrete Full brick Hollow brick |
| Mounting type, anchor, tie | Push-through mounting |