

Technical data sheet

Push-fit plug Delta-Push® for cable ties

Item number: 2351676



Push-fit plug Delta-Push® for mounting electrical installations. Suitable for concrete, calcareous limestone, full brick, hollow brick and porous concrete. Toolless mounting by pushing into a drill hole in a wall or on a ceiling. Without screws. With cable tie seat up to 4.8 mm width and 2 mm high to fasten cables and pipes.



PA Polyamide

Master data

Item number	2351676
Description 1	Push-fit plug
Description 2	for cable tie
Available from	01.02.2025
Manufacturer	OBO
Dimension	35,5x10,0x10,0
Material	Polyamide
Smallest sales unit	100
Unit of quantity	Piece
Weight	0.075 kg
Weight unit	kg/100 pc.


Technical data sheet

Push-fit plug Delta-Push® for cable ties

Item number: 2351676



Dimensions



Length 30 mm

Technical data

Version for	Push-fit anchor
Drill hole depth	35 mm
Drill hole diameter, min.	6 mm
Suitable for fastening with cable ties	yes
Suitable for gas concrete	yes
Suitable for hexagonal wood screw	no
Halogen-free	yes
With edge	yes
With bolts	no
Suitable for material	Calcareous sandstone Porous concrete Concrete Full brick Hollow brick
Mounting type, anchor, tie	Pre-mounting