Technical data sheet Joint connector A2

Item number: 6016642





Screwed version of joint connector for mesh cable trays. Including screw of type FRS M6 x 20. Figure: Positioning and quantity of mesh cable tray connectors.

50-150 mm = 2 units

200-300 mm = 3 units

400–450 mm = 4 units

500-600 mm = 5 units



A2 Stainless steel

2B Bright, treated


Master data

Item number6016642TypeGSV 34 A2Description 1Joint connectorDescription 2for mesh cable trayManufacturerOBOMaterialStainless steelSurfaceBright, treatedSurface standard		
Description 1Joint connectorDescription 2for mesh cable trayManufacturerOBOMaterialStainless steelSurfaceBright, treated	Item number	6016642
Description 2for mesh cable trayManufacturerOBOMaterialStainless steelSurfaceBright, treated	Туре	GSV 34 A2
Manufacturer OBO Material Stainless steel Surface Bright, treated	Description 1	Joint connector
Material Stainless steel Surface Bright, treated	Description 2	for mesh cable tray
Surface Bright, treated	Manufacturer	OBO
	Material	Stainless steel
Surface standard	Surface	Bright, treated
	Surface standard	
Smallest sales unit 20	Smallest sales unit	20
Unit of quantity Piece	Unit of quantity	Piece
Weight 3.1 kg	Weight	3.1 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.

Technical data sheet Joint connector A2

Item number: 6016642





Dimension	34 x 27,5
Length	34 mm
Width	29 mm
Width	1.14 in
Height	24 mm
Height	0.94 in

Technical data

Version for	Otroight compactor
Version for	Straight connector
Maintain electrical functions	no
Suitable for mesh cable tray	yes
Suitable for cable ladder	no
Suitable for cable tray	no
Adjustable connector, horizontal	no
Articulated connector, vertical	no
Suitable for mesh cable tray wire, max.	4.9 mm
Suitable for mesh cable tray wire, min.	3.9 mm
Rustproof steel, pickled	yes
Connection type	Screw connector