

Technical data sheet

Metal spreading anchor

Item number: 3484629



Areas of application: gas concrete, lightweight concrete, Poroton, pumice, plaster, hollow brick and full brick. Can be knocked into porous concrete (gas concrete) of low resistance without drilling. Superbly suited for areas subjected to high temperatures.




St Steel

GTP Electrogalvanized, transparently passivated

Master data

| | |
|---------------------|---|
| Item number | 3484629 |
| Type | MD 6 GTP |
| Description 1 | Metal expanding anchor |
| Manufacturer | OBO |
| Dimension | 6x32mm |
| Material | Steel |
| Surface | Electrogalvanized, transparently passivated |
| Surface standard | |
| Smallest sales unit | 100 |
| Unit of quantity | Piece |
| Weight | 0.25 kg |
| Weight unit | kg/100 pc. |

Dimensions



| | |
|-------------|-------|
| Length | 32 mm |
| Dimension D | 6 mm |
| Dimension L | 32 mm |

Technical data sheet

Metal spreading anchor

Item number: 3484629



Technical data

| | |
|--|--|
| Version for | Spreading anchor |
| Drill hole depth | 38 mm |
| Drill hole diameter, max. | 9 mm |
| Drill hole diameter, min. | 7 mm |
| Suitable for fastening with cable ties | no |
| Suitable for gas concrete | yes |
| Suitable for hexagonal wood screw | no |
| Wood screws | 5-6 |
| With edge | no |
| With bolts | no |
| Suitable for material | Porous concrete Gas concrete Full brick Hollow brick |