

Technical data sheet

Cable tray MKS-Magic® 60, unperforated, black

Item number: 6062996



Unperforated cable tray with integrated quick fastening system. Black coated. Magnetic shield insulation without cover 20 dB, with cover 50 dB.



- St** Steel
- P135** PES135 - Polyester

Master data

| | |
|---------------------|-------------------------------|
| Item number | 6062996 |
| Type | MKSMU 630 FSK SW |
| Description 1 | Cable tray MKSMU |
| Description 2 | unperforated, quick connector |
| Manufacturer | OBO |
| Dimension | 60x300x3050 |
| Colour | Jet black; RAL 9005 |
| Material | Steel |
| Surface | PES135 - Polyester |
| Surface standard | |
| Smallest sales unit | 3 |
| Unit of quantity | Metre |
| Weight | 367.8 kg |
| Weight unit | kg/100 m |


Technical data sheet

Cable tray MKS-Magic® 60, unperforated, black



Item number: 6062996

Dimensions



| | |
|-----------------|----------|
| Dimension | 60 x 300 |
| Length | 3,050 mm |
| Width | 300 mm |
| Height | 60 mm |
| Plate thickness | 1 mm |
| Dimension B | 300 mm |
| Maß W | 300 mm |

Technical data

| | |
|---|-----------------------|
| Connector version | Integrated connector |
| Mounting system fastening type | Floor Ceiling Wall |
| Maintain electrical functions | no |
| With cover | no |
| Mounting perforation in base | no |
| NATO hole pattern | no |
| Usable cross-section | 178 cm ² |
| Usable cross-section | 17800 mm ² |
| Rustproof steel, pickled | no |
| Side perforation | no |
| Wide-span version | no |
| Usable length | 3000 mm |
| Type of connector, cable support system | Click fastening |

Loads

| | |
|-----------------------------------|-----------|
| Insertable support spacings, min. | 1.5 m |
| Insertable support spacings, max. | 2.5 m |
| Support spacing 1.5 m | 1.5 kN/m |
| Support spacing 1.75 m | 1.25 kN/m |
| Support spacing 2.0 m | 1 kN/m |
| Support spacing 2.5 m | 0.5 kN/m |