

Technical data sheet

Flat angle, duct height 80 mm, FS

Item number: 7218066



Flat angle with intumescent fire protection mesh for PYROLINE® Rapid PLM installation duct. Suitable for direct wall and ceiling mounting, mounting below system floors and on support systems. Tool-free joint mounting with PLM SI joint connector. The cover is snapped on without tools, allowing rapid inspection and retroassignment. The cover overhang allows offset cover mounting for continuous equipotential bonding of the entire duct section.



St Steel

FS Strip galvanized

Master data

| | |
|---------------------|---------------------------|
| Item number | 7218066 |
| Description 1 | Flat angle |
| Description 2 | with fire protection mesh |
| Manufacturer | OBO |
| Dimension | 350x350x80 |
| Material | Steel |
| Surface | Strip galvanized |
| Surface standard | DIN EN 10346 |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 166.9 kg |
| Weight unit | kg/100 pc. |

Dimensions

| | |
|-------------|--------|
| Dimension A | 250 mm |
| Dimension B | 100 mm |
| Dimension H | 80 mm |

Technical data sheet

Flat angle, duct height 80 mm, FS

Item number: 7218066



Technical data

| | |
|---------------------------------------|----------------------|
| Number of flammable sides | 4 |
| Cover fastening | Miscellaneous |
| Classification EI – installation duct | 90 |
| With perforation | yes |
| Usable cross-section | 5180 mm ² |
| Partitions possible | no |
| Jacketing | Steel |
| Angle of the bend | 90 ° |