Technical data sheet

Junction box T 40, plug-in seal

Item number: 2007464





Junction box for the connection of cables indoors and in protected outdoor areas. Square design with plug-in seals to the sides and knock-out entries in the bottom. Suitable for wall and ceiling mounting and on mounting panels. With the option to fasten inside. With fixed clamping cover. Made from halogen-free, UV-resistant materials.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 °C. Impact resistance IK07 according to DIN EN 50102.



















Polypropylene

Master data

Item number	2007464
Description 1	Junction box
Description 2	with entries
Manufacturer	OBO
Dimension	90x90x52
Colour	Black
Material	Polypropylene
Smallest sales unit	5
Unit of quantity	Piece
Weight	7 kg
Weight unit	kg/100 pc.
	·


Technical data sheet

Junction box T 40, plug-in seal


Item number: 2007464



Dimensions



Length	90 mm
Width	90 mm
Height	52 mm



Technical data

Expandable	yes		
No. of entries	7		
Type of insertion	Plug-in seal		
Type of entry	Cable		
Type of housing penetration	Cuttable stepped membrane		
Measured insulation voltage Vi	500 V		
Cover	Not transparent		
Cover fastening	Locking		
Entry from rear	yes		
Entries	7 x M25		
Explosion-tested version	no		
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C		
Shape	Square		
Maintain electrical functions	Without		
For Ex zone	Without		
For Ex zone gas	Without		
For Ex zone dust	Without		
Fibre-glass reinforced	no		
Halogen-free	yes		
Clear internal dimensions	77x77x46 mm		
With screening	no		
with lid	yes		
Mounting type	Wall/ceiling mounting		
Nominal cross-section, min.	4 mm ²		
Nominal voltage	500 V		
Sealable	no		
Protection rating	IP56		
Protection rating IK code	IK07.		
Permitted temperature range, max.	60 °C		
Permitted temperature range, min.	-5 °C		

Technical data sheet Junction box T 40, plug-in seal



Item number: 2007464

Technical data		
	Weatherproof	no