

# Technical data sheet

## US 7 support FT

Item number: 6340199



U support in fixed lengths. Dimensions 70 x 50 mm.  
For bracket widths of 400 mm or more, or if the bracket is mounted at the end of a suspended support, we recommend the use of the spacer, type DSK 61.



**St** Steel

**FT** Hot-dip galvanised

### Master data

|                     |                    |
|---------------------|--------------------|
| Item number         | 6340199            |
| Type                | US 7 110 FT        |
| Description 1       | U support          |
| Description 2       | 3-sided perforated |
| Manufacturer        | OBO                |
| Dimension           | 70x50x1100         |
| Material            | Steel              |
| Surface             | Hot-dip galvanised |
| Surface standard    | DIN EN ISO 1461    |
| Smallest sales unit | 1                  |
| Unit of quantity    | Piece              |
| Weight              | 457 kg             |
| Weight unit         | kg/100 pc.         |


# Technical data sheet

US 7 support FT


Item number: 6340199



## Dimensions



|             |             |
|-------------|-------------|
| Dimension   | 70 x 50 x 4 |
| Length      | 1,100 mm    |
| Width       | 70 mm       |
| Height      | 50 mm       |
| Dimension L | 1,100 mm    |



# Technical data sheet

US 7 support FT

Item number: 6340199



## Technical data

|                               |                       |
|-------------------------------|-----------------------|
| Breakable                     | no                    |
| Type of perforation           | 3 sides perforated    |
| Version for                   | Single profile        |
| EPD article                   | yes                   |
| Maintain electrical functions | yes                   |
| Hole width                    | 14 mm                 |
| Material thickness            | 4 mm                  |
| With tothing                  | no                    |
| Profile shape                 | U profile             |
| Slot width                    | 62 mm                 |
| Static value A                | 4.59 cm <sup>2</sup>  |
| Static value Iy               | 13.79 cm              |
| Static value Iz               | 36.84 cm              |
| Static value Wy               | 4.11 cm <sup>2</sup>  |
| Static value Wz               | 10.53 cm <sup>2</sup> |