

Technical data sheet

Surge arrester, 4-pole 385 V

Item number: 5094708



Surge arrester, type 2

- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity to 40 kA (8/20) per pole
- Plug-in arrester with dynamic cut-off unit and visual function display
- High-performance varistor technology

Application: Equipotential bonding (LPZ 1 to 2) in main and sub-distributors.
* Complete = cover and base



Master data


Item number	5094708
Type	V20-C 4-385
Description 1	SurgeController V20
Description 2	4-pole design
Manufacturer	OBO
Dimension	385V
Smallest sales unit	1
Unit of quantity	Piece
Weight	44 kg
Weight unit	kg/100 pc.

Technical data sheet

Surge arrester, 4-pole 385 V

Item number: 5094708

Technical data

	Arrester surge current (8/20 μ s) [total]	80 kA
	Response time	<25 ns
	Blow-out	no
	Version for	4-pole
	Pole version	4
	Structural width in division units (division unit, 17.5 mm)	4
	Operating temperature, max.	80 °C
	Operating temperature, min.	-40 °C
	Remote signalling	no
	Maximum continuous voltage AC	385
	Integrated back-up fuse	no
	Conductor cross-section, flexible (fine-wire), min.	25 mm ²
	Conductor cross-section, rigid (single-wire/multiwire), max.	35 mm ²
	Conductor cross-section, rigid (single-wire/multiwire), min.	2.5 mm ²
	Lightning protection zone LPZ	1→2
	Max. mains-side overcurrent protection	125
	Maximum back-up fuse	125 A
	Maximum discharge current (8/20 μ s)	40 kA
	Installation type	DIN rail 35 mm
	Nominal discharge current (8/20 μ s)	20 kA
Nominal voltage AC (50/60 Hz)	350 V	
Network form	TN	
Test class, type 2	yes	
Protection rating	IP20	
Protection level	≤1,7	
Signalling on device	Visual	
SPD to EN 61643-11	Type 2	
SPD to IEC 61643-1	Class II	